ANNO TAPE COLORS

Indoor · COLORS

Features

- High-density diode-free COB tape, with various monochromatic color options
- IP20 rated, ideal for indoor non-condensing uses
- 5 years warranty

Date | Fixture type

Project name | Project phase

Applications

Under cabinets, coves, theme parks, bedrooms, studios, etc.



Dimensions



Order Code (For LED tape)

Series	Environment	Voltage	Temp./Color	Power
ANNO	**D2-**Dry (IP20)	**24V**-DC24V	**R**-Red **G**-Green **B**-Blue **A**-Amber **P**-Purple **Y**-Yellow **PK**-Pink	**100-**10W/ft

Assembly Builder

Left Feed Entry			
F	Front	**OW**	Open wire 15cm (5.9in.), 20 AWG
C	Closed	**MC**	Male connector with 20cm (0.66ft) cable, 20 AWG
		FC	Female connector with 20cm (0.66ft) cable, 20 AWG
		NA	Only for Closed Feed Entry

Assembly Builder

Right Feed Entry				Length	
F	Front	**OW**	Open wire 3.28ft (1m), 20 AWG	**Max**	10m
C	Closed	**MC**	Open wire 15cm (5.9in.), 20 AWG		
		FC	Male connector with 20cm (0.66ft) cable, 20 AWG	**Increment**	50mm(1.97in.)
		NA	Female connector with 20cm (0.66ft) cable, 20 AWG		

*For customizations, please inquire.

Extrusion Order Code

Product Code	Colors	Lens	Lengths
Please select on the Extrusion Compatibility page	**S** = Silver anodized **W** = White lacquered **B** = Black anodized	**OP** - Opal **FR** - Frosted **CL** - Clear	**1m**(3.28ft) **2m**(6.56ft)

*For custom RAL colors, please inquire.

*Extrusions are sold separately. Refer to corresponding spec sheets for ordering info on extrusions and their accessories (endcaps, mounting brackets, etc.)

Lumen Output (lm/m)

Temp./Color	10W/M
Red	180
Green	1132
Blue	218
Amber	250
Purple	559
Yellow	495
Pink	689
Max. Run Length(M)	10

Technical Details	
Width	10mm(0.39in.)
LED Quantity	480 LEDs/M (146 LEDs/ft)
Beam Angle	180°
Efficacy	181m/W @Red 10W
Average Life (L70)	> 54,000 hours
Max. Length Per Reel	30m (98.4ft)
Storage Temperature	-20℃~ 60℃
Ambient Temperature	-20℃~ 45℃

Feed Entry Options

F: Front



C: Closed



Connector Wire Options

OW: Open wire, **Dry only**
Standard 15cm(0.59in.), 20 AWG
(wire length customizable)



MC: Male connector, **Dry**, Standard 20cm(0.66ft), 20 AWG



FC: Female connector, **Dry**, Standard 20cm(0.66ft), 20 AWG

Channel Compatibility

Lens Type & Light Transmission

ANNO TAPE COLORS

Indoor · COLORS


* Non-standard option, please contact us for customization support.

CL Clear FR Frosted OP Opal

Surface


BE1202

CL 51% FR 47% OP 38%




BE1302

CL 70% FR 64% OP 53%




BE1415

CL 44% FR 40% OP 33%




BE1919

CL 65% FR 60% OP 49%




BE2020

CL 64% FR 58% OP 48%



BE2601


CL 73% FR 67% OP 55%



Mud-In


BE5615

CL 49% FR 45% OP 37%



BE7615


CL 60% FR 55% OP 45%



Recessed


BE1201

CL 50% FR 46% OP 38%




BE1207

CL 50% FR 46% OP 37%




BE2015

CL 45% FR 41% OP 34%



BE5035

CL 54% FR 49% OP 40%




BE6575

CL 55% FR 50% OP 41%

ANNO TAPE COLORS


Indoor · COLORS



Corner


BE1001

CL 77% FR 70% OP 57%




BE1002

CL 76% FR 69% OP 57%



BE1101


CL 49% FR 44% OP 36%



Suspended


BE5075

CL 55% FR 50% OP 41%




BE60

CL 80% FR 73% OP 60%



BE3535

CL 46% FR 42% OP 35%



Specialty

BE1806

Bendable surface mounted

CL 77% FR 70% OP 57%

BE2009

Coves

CL 49% FR 45% OP 36%

BE4615

Borderless Inside Corner

CL 51% FR 46% OP 38%


BE5315


Borderless Outside Corner


CL 49% FR 45% OP 31%


ANNO TAPE COLORS

Indoor · COLORS











BE6728
Staircase

CL 45% FR 41% OP 34%



BE8833
Cove Recessed /
Double-Layer Borderless

CL 52% FR 48% OP 39%



Connectors & Additional Accessories (Optional, purchase for extra)

N6012-STCN-2P-10
Strip to cable connector without wire, for 10mm (0.39in.) tape, 2 pin



N6012-STC-2P-10
Strip to cable connector with 15cm (5.91in.) wire, for 10mm (0.39in.) tape, 2 pin



N6012-STSJ-2P-10
Strip to strip jumper connector with 15cm (5.91in.) wire, for 10mm (0.39in.) tape, 2 pin



N6012-STDCB-2P-10
Strip to cable with black male & female connector, for 10mm (0.39in.) tape, 2 pin



N6012-STDCW-2P-10
Strip to cable with white male & female connector, for 10mm (0.39in.) tape, 2 pin

N14CO-STS-2P-10
Strip to strip connector, for 10mm (0.39in.) tape, 2 pin



C14CO-LC-2P-10
L-shaped corner connector, for 10mm (0.39in.) tape, 2 pin



C14CO-RC-2P-10
R-shaped corner connector, for 10mm (0.39in.) tape, 2 pin

N16CO-L-2P-10
L-shaped connector, for 10mm (0.39in.) tape, 2 pin



MC-2P-20
Male SM connector with 20cm(0.66ft) cable, 2pin, IP20,Dry, 20AWG



FC-2P-20
Female SM connector with 20cm(0.66ft) cable, 2pin, IP20, Dry, 20AWG



VHB
VHB 3M adhesive back tape, stronger stickiness

ANNO TAPE COLORS

Indoor · COLORS

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
XLG-150-24-A	150W	100-305VAC	24V	Dry/Damp/IP67	180 * 63 * 35.5 mm
LPV-150-24	150W	180-305VAC		Dry/Damp/IP67	148 * 40 * 30 mm
LRS-150-24	150W	85-132VAC / 170-264VAC		Dry	99 * 97 * 30 mm

3 in 1-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
PWM-120-24	120W	90-305VAC		Dry/Damp/IP67	191 * 63 * 37.5 mm

DALI-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24DA-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

Wiring Diagram

Non-dimmable



3 in 1-dimmable



DALI-dimmable



ANNO TAPE COLORS

Indoor · COLORS

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	484.0m	304.5m	191.4m	120.4m	75.5m	47.5m	29.8m	18.5m
20W / 0.8A	242.0m	152.1m	95.7m	60.0m	37.8m	23.7m	14.9m	9.1m
30W / 1.3A	161.2m	101.5m	63.7m	39.9m	24.9m	15.8m	9.7m	6.1m
40W / 1.7A	121.0m	75.9m	47.8m	29.8m	18.9m	11.8m	7.3m	4.5m
50W / 2.1A	96.6m	60.6m	38.1m	24.0m	14.9m	9.4m	5.7m	3.6m
60W / 2.5A	80.4m	50.6m	31.7m	19.8m	12.5m	7.9m	4.8m	3.0m
70W / 2.9A	68.8m	43.2m	27.1m	17.0m	10.6m	6.7m	4.2m	2.4m
80W / 3.3A	60.3m	37.8m	23.7m	14.9m	9.4m	5.7m	3.6m	2.1m
90W / 3.8A	53.6m	33.8m	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m
100W / 4.2A	48.1m	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m
110W / 4.6A	43.8m	27.4m	17.3m	10.6m	6.7m	4.2m	2.7m	1.5m
120W / 5.0A	40.2m	25.3m	15.8m	9.7m	6.1m	3.9m	2.4m	1.5m
130W / 5.4A	37.1m	23.1m	14.6m	9.1m	5.7m	3.6m	2.1m	1.2m
140W / 5.8A	34.4m	21.6m	13.4m	8.5m	5.1m	3.3m	2.1m	1.2m
150W / 6.3A	32.0m	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m
160W / 6.7A	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m	0.9m
170W / 7.1A	28.3m	17.6m	10.9m	7.0m	4.2m	2.7m	1.5m	0.9m
180W / 7.5A	26.8m	16.7m	10.3m	6.7m	3.9m	2.4m	1.5m	0.9m
190W / 7.9A	25.3m	15.8m	10.0m	6.0m	3.9m	2.4m	1.5m	0.9m
200W / 8.3A	24.0m	14.9m	9.4m	5.7m	3.6m	2.1m	1.2m	0.9m
210W / 8.8A	22.8m	14.3m	8.8m	5.4m	3.3m	2.1m	1.2m	0.6m
220W / 9.2A	21.9m	13.7m	8.5m	5.4m	3.3m	2.1m	1.2m	0.6m
230W / 9.6A	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m	1.2m	0.6m
240W / 10.0A	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m	0.6m
250W / 10.4A	19.2m	12.1m	7.6m	4.5m	2.7m	1.8m	0.9m	0.6m