Beamever

LINIO NEON 1617 TW

Designer's Custom Playground

Outdoor · Vertical Bending · Horizontal Bending · Tunable White

Features


- Robust & uniform silicone body, tunable white from 2700K to 5300K
- IP68 rated, ideal for outdoor uses, not for underwater project
- 5 years warranty


Date | Fixture type

Project name | Project phase


Applications

Hotels, facades, gardens, parks, balconies, roofs, soffits, etc.






Bending Directions & Diameters





TV - Top View
(Vertical Bending)



SV - Side View
(Horizontal Bending)

Dimensions





Order Code

Model	Environment	Voltage	CCT	Power	End Cap
LN1617TV **LN1617SV**	**W8**-Wet (IP68)	**24V**-DC24V	**27K53K**-2700K+5300K	**130**-13W/M	**FT** Flush Translucent **FO** Flush Opaque

Assembly Builder

Left Feed Entry	
F Front	**OW** Open wire 300mm (11.81in.)
B Bottom	**OA** Open Wire with Anti-Wicking Ferrule
S Side	**MC** Male connector with 300mm (11.81in.) cable
C Closed	**FC** Female connector with 300mm (11.81in.)cable
	NA Only for Closed Feed Entry

Assembly Builder

Right Feed Entry			Length	
F Front	**OW**	Open wire 300mm (11.81in.)	**Max. nominal**	15m (49.2ft)
B Bottom	**OA**	Open Wire with Anti-Wicking Ferrule		
S Side	**MC**	Male connector with 300mm (11.81in.) cable	**Increment**	71.4mm(2.81in.)
C Closed	**FC**	Female connector with 300mm (11.81in.)cable		
	NA	Only for Closed Feed Entry		

*We will list the nearest actual manufacturing length on the quotation, based on your requested length.

Mounting Order Code

Product Code
Please select on the Mounting Options page

LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White

Lumen Output (lm/m)


CCT	Vertical Bending	Horizontal Bending
	13W/M	13W/M
2700K	480	416
5300K	498	436
2700K+5300K	980	848
Max. Run Length	15m	15m

Techinical Details

Parameter	Vertical Bending	Horizontal Bending
Efficacy	75.4lm/W @2700K+5300K 13W	65.2lm/W @2700K+5300K 13W
CRI	Ra≥90	Ra≥90
Beam Angle	110°	110°
LED MacAdam	2 steps	2 steps
IK Rating	IK10 (with aluminium profile)	IK10 (with aluminium profile)
Average Life (L80B10)	>56,000 hours	>56,000 hours
Storage Temperature	-40°C~ 65°C	-40°C~ 65°C
Operating Temperature	-40°C~ 65°C	-40°C~ 65°C

Photometry


LN1617TV-W8-24V-27K53K-130-FT-F-OW-F-OW
LINIO NEON 1617 TV TW, Vertical bend, 2700K+5300K, 13W/M



Zonal Lumen Summary

Zone	Lumen	% Fixture
0-30	259.3	26.4%
0-40	424.1	43.2%
0-60	749.2	76.4%
0-90	968.1	98.7%
0-180	980.5	100.0%

LN1617SV-W8-24V-27K53K-130-FT-F-OW-F-OW
LINIO NEON 1617 SV TW, Horizontal bend, 2700K+5300K, 13W/M



Zonal Lumen Summary


Zone	Lumen	% Fixture
0-30	223.4	26.3%
0-40	365.1	43.0%
0-60	644.7	76.0%
0-90	837.0	98.6%
0-180	848.7	100.0%


LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White


Feed Entry / End Cap Options


FT: Flush Translucent – IP68, factory-made only







FO: Flush Opaque – IP68, factory-made only







Silicone end cap – IP67, for field cuttable only





Mechanical end cap with screws – IP67, for field cuttable only







Connector Wire Options




OW: Open wire, **Dry only**
Standard 300mm (11.81in.),18 AWG,
wire length customizable



MC: Male connector, **Wet**
Standard 300mm (11.81in.), 18 AWG





FC: Female connector, **Wet**
Standard 300mm (11.81in.), 18 AWG



OA: Open Wire with **Anti-Wicking Ferrule, Wet**
Standard 300mm (11.81in.),18 AWG,
Protects against water ingress through the power cable



Mounting Options



NF1617-SC



Name	Straight surface channel
Material	Aluminum
Standard Length	1m (3.28ft)




NF1617-BC


Name	Bendable surface channel
Material	Aluminum
Standard Length	1m (3.28ft)
Min. Bending Diameter	600mm(23.6in.)



NF1617-RC


Name	Straight recessed channel
Material	Aluminum
Standard Length	1m (3.28ft)



NF1617-MC


Name	Mud-in channel
Material	Aluminum
Standard Length	1m (3.28ft)




NF1617-BMC



Name	Bendable mud-in channel
Material	Aluminum
Standard Length	1m (3.28ft)
Min. Top Bending Diameter	600mm(23.6in.)
Min. Side Bending Diameter	1600mm(63in.)



NF1617-SCS


Name	Straight surface channel
Material	Aluminum with silicone groove
Standard Length	1m (3.28ft)



NF1617-LBC

Name	Light-block channel
Material	Aluminum
Standard Length	1m (3.28ft)







NF1617-PC

Name	PC channel
Material	Polycarbonate
Standard Length	1m (3.28ft)



Mounting Options




NF1617-BPC


Name	Bendable surface channel
Material	Polycarbonate
Standard Length	1m (3.28ft)
Min. Bending Radius	150mm (5.91in.)



NF1617-CL

Name	Mounting clip
Material	Aluminum
Standard Length	25mm (0.98in.)








NF1617-LS

Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	20mm(0.79in.)

* NF1617-LS must be installed with NF1617-SC









NF1617-AC

Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	25.5mm (1 in.)

* NF1617-AC must be installed with NF1617-SC




NF1617-RC-SPC


Name	Spring clip
Standard Pkg	1pcs

* NF1617-RC-SPC must be installed with NF1617-RC


LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White


Silicone End Caps (Optional, purchase for extra)



NF1617-SEC-C
Silicone closed end cap



NF1617-SEC-F-3P
Silicone end cap front entry with 300mm (11.81in.) cable, 3 pin




NF1617-SEC-S-3P
Silicone end cap side entry with 300mm (11.81in.) cable, 3 pin




NF1617-SEC-B-3P
Silicone end cap bottom entry with 300mm (11.81in.) cable, 3 pin


Solderless & Glueless Mechanical End Caps for Vertical Bending(Optional, purchase for extra)




NF1617T-MEC-LF-3P
Mechanical end cap with screws, left front entry, 300mm (11.81in.) cable, 3 pin, IP67



NF1617T-MEC-RF-3P
Mechanical end cap with screws, right front entry, 300mm (11.81in.) cable, 3 pin, IP67



NF1617T-MEC-LS-3P
Mechanical end cap with screws, left side entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617T-MEC-RS-3P
Mechanical end cap with screws, right side entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617T-MEC-LB-3P
Mechanical end cap with screws, left bottom entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617T-MEC-RB-3P
Mechanical end cap with screws, right bottom entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617T-MEC-C
Mechanical closed end cap with screws, IP67



NF1617T-S-S-3P
Strip to strip connector, 3 pin, IP54



NF1617T-JC-F-3P
Jumper connector front entry, 150mm (5.9in.) cable, 3 pin, IP67



NF1617T-JC-S-3P
Jumper connector side entry, 150mm (5.9in.) cable, 3 pin, IP67




NF1617T-JC-B-3P
Jumper connector bottom entry, 150mm (5.9in.) cable, 3 pin, IP67


LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White


Solderless & Glueless Mechanical End Caps for Horizontal Bending(Optional, purchase for extra)




NF1617S-MEC-LF-3P
Mechanical end cap with screws, left front entry, 300mm (11.81in.) cable, 3 pin, IP67



NF1617S-MEC-RF-3P
Mechanical end cap with screws, right front entry, 300mm (11.81in.) cable, 3 pin, IP67



NF1617S-MEC-LS-3P
Mechanical end cap with screws, left side entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617S-MEC-RS-3P
Mechanical end cap with screws, right side entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617S-MEC-LB-3P
Mechanical end cap with screws, left bottom entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617S-MEC-RB-3P
Mechanical end cap with screws, right bottom entry, 300mm (11.81in.) cable, 3 pin, IP67




NF1617S-MEC-C
Mechanical closed end cap with screws, IP67



NF1617S-S-S-3P
Strip to strip connector, 3 pin, IP54



NF1617S-JC-F-3P
Jumper connector front entry, 150mm (5.9in.) cable, 3 pin, IP67



NF1617S-JC-S-3P
Jumper connector side entry, 150mm (5.9in.) cable, 3 pin, IP67



NF1617S-JC-B-3P
Jumper connector bottom entry, 150mm (5.9in.) cable, 3 pin, IP67

Additional Accessories (Optional, purchase for extra)



MCW-3P-67
Male connector, 300mm (11.81in.) white cable, 3 pin, IP67, Wet, 18 AWG



FCW-3P-67
Female connector, 300mm (11.81in.) white cable, 3 pin, IP67, Wet, 18 AWG




MCB-3P-67
Male connector, 300mm (11.81in.) black cable, 3 pin, IP67, Wet, 18 AWG



FCB-3P-67
Female connector, 300mm (11.81in.) black cable, 3 pin, IP67, Wet, 18 AWG



ADJS
1 Adjustable Angle Scissors Set, with 4 Spare Blades



NF1617-IT
Installation tool for NF1617-BPC

LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24A-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
LRS-150-24	150W	85-132VAC / 170-264VAC	24V	Dry	159 * 97 * 30 mm

0-10V Dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
LM-100-24-G2A2	100W	220-240VAC	24V	Dry	293 *43 *30mm

DALI-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
LM-100-24-G2D2	100w	220-240VAC	24V	Dry	293 *43 *30mm

Controller Options


Type	Code	Description	Environment	Size (L x W x H)
Controllers	M2+M3-3A	3 channels output, Max. 3A current per channel, up to 216W output power	Indoor	135 * 30 * 20 mm

Wiring Diagram


Non-dimmable



0-10V Dimmable



DALI-dimmable



LINIO NEON 1617 TW

Outdoor · Vertical Bending · Horizontal Bending · Tunable White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	484.0m	304.5m	191.4m	120.4m	75.5m	47.5m	29.8m	18.5m
20W / 0.8A	242.0m	152.1m	95.7m	60.0m	37.8m	23.7m	14.9m	9.1m
30W / 1.3A	161.2m	101.5m	63.7m	39.9m	24.9m	15.8m	9.7m	6.1m
40W / 1.7A	121.0m	75.9m	47.8m	29.8m	18.9m	11.8m	7.3m	4.5m
50W / 2.1A	96.6m	60.6m	38.1m	24.0m	14.9m	9.4m	5.7m	3.6m
60W / 2.5A	80.4m	50.6m	31.7m	19.8m	12.5m	7.9m	4.8m	3.0m
70W / 2.9A	68.8m	43.2m	27.1m	17.0m	10.6m	6.7m	4.2m	2.4m
80W / 3.3A	60.3m	37.8m	23.7m	14.9m	9.4m	5.7m	3.6m	2.1m
90W / 3.8A	53.6m	33.8m	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m
100W / 4.2A	48.1m	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m
110W / 4.6A	43.8m	27.4m	17.3m	10.6m	6.7m	4.2m	2.7m	1.5m
120W / 5.0A	40.2m	25.3m	15.8m	9.7m	6.1m	3.9m	2.4m	1.5m
130W / 5.4A	37.1m	23.1m	14.6m	9.1m	5.7m	3.6m	2.1m	1.2m
140W / 5.8A	34.4m	21.6m	13.4m	8.5m	5.1m	3.3m	2.1m	1.2m
150W / 6.3A	32.0m	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m
160W / 6.7A	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m	0.9m
170W / 7.1A	28.3m	17.6m	10.9m	7.0m	4.2m	2.7m	1.5m	0.9m
180W / 7.5A	26.8m	16.7m	10.3m	6.7m	3.9m	2.4m	1.5m	0.9m
190W / 7.9A	25.3m	15.8m	10.0m	6.0m	3.9m	2.4m	1.5m	0.9m
200W / 8.3A	24.0m	14.9m	9.4m	5.7m	3.6m	2.1m	1.2m	0.9m
210W / 8.8A	22.8m	14.3m	8.8m	5.4m	3.3m	2.1m	1.2m	0.6m
220W / 9.2A	21.9m	13.7m	8.5m	5.4m	3.3m	2.1m	1.2m	0.6m
230W / 9.6A	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m	1.2m	0.6m
240W / 10.0A	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m	0.6m
250W / 10.4A	19.2m	12.1m	7.6m	4.5m	2.7m	1.8m	0.9m	0.6m