# AERO TAPE WET X

Indoor · Static White

## Features

- Various output & CCT options
- IP67 rated, ideal for outdoor uses
- 5 years warranty

Date

Fixture type

Project name

Project phase

## Applications

Gardens, parks, decks, patios, pathways, outdoor steps, etc.



## Dimensions




## Order Code

| Model | Environment | Voltage | CCT | Power |
|---|---|---|---|---|
| **AERO** | **W7**-Wet (IP67) | **24V**-DC24V | **22K**-2200K<br>**24K**-2400K<br>**27K**-2700K<br>**30K**-3000K<br>**35K**-3500K<br>**40K**-4000K<br>**65K**-6500K | **048**-4.8W/M<br>**096**-9.6W/M<br>**144**-14.4W/M<br>**192**-19.2W/M<br>**240**-24W/M |

## Assembly Builder

| Left Feed Entry | | | |
|---|---|---|---|
| **F** | Front | **OW** | Open wire 150mm(5.9in.) |
| **C** | Closed | **MC** | Male connector with 200mm(7.87in.) cable |
| | | **FC** | Female connector with 200mm(7.87in.) cable |
| | | **NA** | Only for Closed Feed Entry |

## Assembly Builder

| Right Feed Entry | | | |
|---|---|---|---|
| **F** | Front | **OW** | Open wire 150mm(5.9in.) |
| **C** | Closed | **MC** | Male connector with 200mm(7.87in.) cable |
| | | **FC** | Female connector with 200mm(7.87in.) cable |
| | | **NA** | Only for Closed Feed Entry |

| Length | |
|---|---|
| **Increment** | 50mm (1.97in.) |

*We will list the nearest actual manufacturing length on the quotation, based on your requested length.

## Channel Order Code

| Product Code | Colors* | Lens | Clip* | Length |
|---|---|---|---|---|
| Please select on the Extrusion Compatibility page | ■ **S** Silver anodized<br>□ **W** White lacquered<br>■ **B** Black anodized | **OP** Opal<br>**FR** Frosted<br>**CL** Clear | **MCL** Metal clip<br>**PCL** Plastic clip<br>**ACL** Adjustable angle clip | 1m(3.28ft)<br>2m (6.56ft) |

*For custom RAL colors, please inquire.
*Please refer to the Channel Compatibility page for compatible clip options.

# AERO TAPE WET X

Indoor · Static White

## Lumen Output (lm/m)

| CCT | 4.8W/M | 9.6W/M | 14.4W/M | 19.2W/M | 24W/M |
|---|---|---|---|---|---|
| 2200K | 340 | 640 | 920 | 1160 | 1390 |
| 2400K | 360 | 670 | 980 | 1230 | 1470 |
| 2700K | 380 | 710 | 1030 | 1300 | 1550 |
| 3000K | 400 | 750 | 1090 | 1370 | 1630 |
| 3500K | 415 | 780 | 1130 | 1420 | 1700 |
| 4000K | 430 | 800 | 1160 | 1470 | 1740 |
| 6500K | 410 | 760 | 1110 | 1400 | 1660 |
| Max. Run Length | 9m | 7m | 6m | 6m | 5m |

## Techinical Details

| | |
|---|---|
| Width | 12mm (0.47in. ) |
| LED Quantity | 120 LEDs/M (36 LEDs/ft ) |
| Beam Angle | 120° |
| Efficacy | 78lm/W @3000K 9.6W |
| CRI | Ra≥90 |
| LED MacAdam | 3 steps |
| Average Life (L70) | >54,000 hours |
| Max. Length Per Reel | 30m(98.4ft) |
| Storage Temperature | -25°C~ 60°C |
| Ambient Temperature | -25°C~ 45°C |

## Feed Entry Options



**F:** Front



**C:** Closed

## Connector Wire Options



**OW:** Open wire, **Dry only**
Standard 150mm(5.9in.),22 AWG,
wire length customizable



**MC:** Male connector, **Wet**
Standard 200mm(7.87in.), 22 AWG



**FC:** Female connector, **Wet**
Standard 200mm(7.87in.), 22 AWG

# AERO TAPE WET X

Indoor · Static White

## Channel Compatibility

*Non-standard option, please contact us for customization support.

| Lens Type & Light Transmission | | |
|---|---|---|
| CL Clear | FR Frosted | OP Opal |

### Surface

#### BE1202

CL 55% FR 50% OP 41%




Accommodates 1 LED strip

Clip Options:
Metal/Plastic/Adjustable angle clip

#### BE1919

CL 67% FR 61% OP 50%




Accommodates 1 LED strip

Clip Options:
Metal clip

### Mud-in

#### BE5615

CL 49% FR 45% OP 37%




Accommodates 1 LED strip

Clip Options:
N/A

# AERO TAPE WET X

Indoor · Static White

## Recessed

| BE1201 | BE1207 | BE5035 | BE6575 |
|---|---|---|---|
| CL 53% FR 49% OP 40% | CL 52% FR 48% OP 39% | CL 46% FR 42% OP 35% | CL 56% FR 51% OP 42% |
|  |  |  |  |
| Accommodates 1 LED strip | Accommodates 1 LED strip | Accommodates up to 2 LED strips | Accommodates up to 2 LED strips |
| Clip Options:<br>Metal/Plastic clip | Clip Options:<br>Spring clip | Clip Options:<br>Spring clip | Clip Options:<br>N/A |

## Corner

| BE1203 |
|---|
| CL 64% FR 59% OP 48% |
|  |
| Accommodates 1 LED strip |
| Clip Options:<br>Metal/Plastic clip |

## Suspended

| BE3535 | BE5075 | BE60 |
|---|---|---|
| CL 48% FR 44% OP 36% | CL 55% FR 51% OP 41% | CL 78% FR 72% OP 59% |
|  |  |  |
| Accommodates up to 2 LED strips | Accommodates up to 2 LED strips | Accommodates up to 2 LED strips |
| Clip Options:<br>Metal clip | Clip Options:<br>Metal clip | Clip Options:<br>Metal clip |

# AERO TAPE WET X

Indoor · Static White

## Connectors & Additional Accessories(Optional, purchase for extra)



**CL-12**
Mounting clip,
for 12mm (0.47in.) tape



**SEC-C-12-67**
Closed silicone end cap,
for 12mm (0.47in.) tape,
IP67 with glue sealing



**JST-M-2P-67**
Male connector,
200mm(7.87in.) red&black cable,
2 pin, IP67, 22 AWG



**JST-F-2P-67**
Female connector,
200mm(7.87in.) red&black cable,
2 pin, IP67, 22 AWG



**VHB**
VHB 3M adhesive back tape, stronger stickiness

# AERO TAPE WET X

Indoor · Static White

## Drivers

### Non-dimmable

| Code | Max Load | Input | Output | Environment | Size (L x W x H) |
|---|---|---|---|---|---|
| ELG-150-24A-3Y | 150W | 100-305VAC | 24V | Dry/Damp/IP67 | 219 * 63 * 35.5 mm |
| LRS-150-24 | 150W | 85-132VAC / 170-264VAC | 24V | Dry | 159 * 97 * 30 mm |

### 3 in 1-dimmable

| Code | Max Load | Input | Output | Environment | Size (L x W x H) |
|---|---|---|---|---|---|
| ELG-150-24B-3Y | 150W | 100-305VAC | 24V | Dry/Damp/IP67 | 219 * 63 * 35.5 mm |

### DALI-dimmable

| Code | Max Load | Input | Output | Environment | Size (L x W x H) |
|---|---|---|---|---|---|
| ELG-150-24DA-3Y | 150W | 100-305VAC | 24V | Dry/Damp/IP67 | 219 * 63 * 35.5 mm |

## Wiring Diagram

### Non-dimmable




### 3 in 1-dimmable




### DALI-dimmable



# AERO TAPE WET X

Indoor · Static White

## 24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

| Total load | 8AWG | 10AWG | 12AWG | 14AWG | 16AWG | 18AWG | 20AWG | 22AWG |
|---|---|---|---|---|---|---|---|---|
| 10W / 0.4A | 484.0m | 304.5m | 191.4m | 120.4m | 75.5m | 47.5m | 29.8m | 18.5m |
| 20W / 0.8A | 242.0m | 152.1m | 95.7m | 60.0m | 37.8m | 23.7m | 14.9m | 9.1m |
| 30W / 1.3A | 161.2m | 101.5m | 63.7m | 39.9m | 24.9m | 15.8m | 9.7m | 6.1m |
| 40W / 1.7A | 121.0m | 75.9m | 47.8m | 29.8m | 18.9m | 11.8m | 7.3m | 4.5m |
| 50W / 2.1A | 96.6m | 60.6m | 38.1m | 24.0m | 14.9m | 9.4m | 5.7m | 3.6m |
| 60W / 2.5A | 80.4m | 50.6m | 31.7m | 19.8m | 12.5m | 7.9m | 4.8m | 3.0m |
| 70W / 2.9A | 68.8m | 43.2m | 27.1m | 17.0m | 10.6m | 6.7m | 4.2m | 2.4m |
| 80W / 3.3A | 60.3m | 37.8m | 23.7m | 14.9m | 9.4m | 5.7m | 3.6m | 2.1m |
| 90W / 3.8A | 53.6m | 33.8m | 21.0m | 13.1m | 8.2m | 5.1m | 3.0m | 1.8m |
| 100W / 4.2A | 48.1m | 30.1m | 18.9m | 11.8m | 7.3m | 4.5m | 2.7m | 1.8m |
| 110W / 4.6A | 43.8m | 27.4m | 17.3m | 10.6m | 6.7m | 4.2m | 2.7m | 1.5m |
| 120W / 5.0A | 40.2m | 25.3m | 15.8m | 9.7m | 6.1m | 3.9m | 2.4m | 1.5m |
| 130W / 5.4A | 37.1m | 23.1m | 14.6m | 9.1m | 5.7m | 3.6m | 2.1m | 1.2m |
| 140W / 5.8A | 34.4m | 21.6m | 13.4m | 8.5m | 5.1m | 3.3m | 2.1m | 1.2m |
| 150W / 6.3A | 32.0m | 20.1m | 12.5m | 7.9m | 4.8m | 3.0m | 1.8m | 1.2m |
| 160W / 6.7A | 30.1m | 18.9m | 11.8m | 7.3m | 4.5m | 2.7m | 1.8m | 0.9m |
| 170W / 7.1A | 28.3m | 17.6m | 10.9m | 7.0m | 4.2m | 2.7m | 1.5m | 0.9m |
| 180W / 7.5A | 26.8m | 16.7m | 10.3m | 6.7m | 3.9m | 2.4m | 1.5m | 0.9m |
| 190W / 7.9A | 25.3m | 15.8m | 10.0m | 6.0m | 3.9m | 2.4m | 1.5m | 0.9m |
| 200W / 8.3A | 24.0m | 14.9m | 9.4m | 5.7m | 3.6m | 2.1m | 1.2m | 0.9m |
| 210W / 8.8A | 22.8m | 14.3m | 8.8m | 5.4m | 3.3m | 2.1m | 1.2m | 0.6m |
| 220W / 9.2A | 21.9m | 13.7m | 8.5m | 5.4m | 3.3m | 2.1m | 1.2m | 0.6m |
| 230W / 9.6A | 21.0m | 13.1m | 8.2m | 5.1m | 3.0m | 1.8m | 1.2m | 0.6m |
| 240W / 10.0A | 20.1m | 12.5m | 7.9m | 4.8m | 3.0m | 1.8m | 1.2m | 0.6m |
| 250W / 10.4A | 19.2m | 12.1m | 7.6m | 4.5m | 2.7m | 1.8m | 0.9m | 0.6m |